



Minimum Evaporating Temp. With:

- 25 °C Suction Gas Return
- Maximum Evaporating Temperature

Suction Superheat 10.0K

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	19.60	25.40	32.30						
15.0	18.15	23.70	30.30	38.20					
20.0	16.65	21.90	28.30	35.80	44.60				
25.0	15.15	20.20	26.30	33.40	41.80	51.50			
30.0	13.70	18.50	24.30	31.10	39.10	48.30	52.40	59.00	64.90
35.0	12.25	16.85	22.30	28.70	36.30	45.10	49.00	55.20	60.90
40.0	10.85	15.20	20.40	26.40	33.60	41.90	45.60	51.50	56.90
45.0	9.57	13.65	18.45	24.20	30.90	38.70	42.20	47.80	52.90
50.0	8.35	12.15	16.65	22.00	28.20	35.60	38.90	44.20	49.00
55.0	7.24	10.75	14.90	19.85	25.70	32.50	35.60	40.60	45.10
60.0	6.24	9.47	13.30	17.80	23.20	29.60	32.40	37.10	41.30
62.0			12.65	17.00	22.20	28.40	31.20	35.70	39.80

Cond °C	Power, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	5.39	5.60	5.61						
15.0	5.67	6.03	6.21	6.18					
20.0	5.88	6.38	6.73	6.89	6.81				
25.0	6.04	6.67	7.18	7.51	7.64	7.51			
30.0	6.15	6.91	7.57	8.07	8.39	8.49	8.46	8.32	8.12
35.0	6.24	7.11	7.90	8.57	9.08	9.39	9.45	9.46	9.39
40.0	6.30	7.28	8.20	9.03	9.72	10.25	10.35	10.50	10.55
45.0	6.34	7.42	8.47	9.44	10.30	11.00	11.25	11.50	11.70
50.0	6.39	7.56	8.72	9.83	10.85	11.75	12.05	12.45	12.75
55.0	6.45	7.70	8.97	10.20	11.40	12.45	12.85	13.40	13.75
60.0	6.53	7.85	9.22	10.60	11.90	13.15	13.60	14.25	14.75
62.0			9.32	10.75	12.10	13.40	13.90	14.60	15.15

Cond °C	Current at 400 V, A								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	15.01	15.23	15.20						
15.0	14.64	15.03	15.21	15.14					
20.0	14.39	14.94	15.33	15.50	15.39				
25.0	14.23	14.95	15.54	15.94	16.11	15.98			
30.0	14.16	15.03	15.81	16.45	16.88	17.06	17.04	16.92	16.72
35.0	14.13	15.15	16.12	16.99	17.69	18.16	18.28	18.37	18.35
40.0	14.13	15.30	16.46	17.54	18.50	19.27	19.52	19.81	19.97
45.0	14.14	15.45	16.79	18.09	19.30	20.36	20.74	21.23	21.57
50.0	14.13	15.58	17.08	18.60	20.06	21.41	21.91	22.60	23.11
55.0	14.08	15.66	17.33	19.05	20.75	22.39	23.01	23.90	24.59
60.0	13.96	15.67	17.51	19.42	21.37	23.28	24.02	25.10	25.96
62.0			17.55	19.55	21.58	23.60	24.39	25.55	26.48

Cond °C	Suction Mass Flow, g/s								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	108.50	138.00	172.50						
15.0	104.50	133.50	168.00	208.00					
20.0	99.80	129.00	163.50	203.00	248.00				
25.0	95.00	124.00	158.50	197.50	242.00	293.00			
30.0	89.80	119.00	153.00	192.00	236.00	287.00	309.00	344.00	375.00
35.0	84.50	113.50	147.50	186.00	230.00	280.00	302.00	336.00	367.00
40.0	79.10	108.00	141.50	179.50	223.00	273.00	294.00	329.00	359.00
45.0	73.70	102.50	135.50	173.00	216.00	265.00	287.00	321.00	351.00
50.0	68.40	97.00	129.50	166.50	209.00	257.00	279.00	312.00	343.00
55.0	63.40	91.60	123.50	160.00	202.00	250.00	271.00	304.00	334.00
60.0	58.80	86.50	118.00	153.50	194.50	242.00	262.00	295.00	325.00
62.0			115.50	151.00	192.00	238.00	259.00	292.00	321.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	4
Displacement @ 50 Hz, m³/h	70.8
Bore/Stroke, mm	68.3/55.6
Length/Width, mm	670/490
Height, mm	495
Net Weight, kg	181
Gross Weight, kg	197
Suction, inch	1 5/8
Discharge, inch	1 1/8
Drive Frequency Range, Hz	25 - 60
Oil Quantity, l	3.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	1430
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	27
Locked Rotor Current, A	156
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Mounting Springs	4
Oil Pressure Switch	OPS2 Sensor

ACCESSORIES OPTIONAL

Capacity Control	Capacity Steps 50%
Check Valve	For unloaded start operation
Additional Cooling	70 W Vertical Air Flow Fan
Crankcase Heater	100 W Internal
Discharge Temperature Protection	Head PTC sensor
Unloaded start	Available
Deep Oil Sump	Mounted
Enclosure Class	IP 56
Adapter Kit	For Parallel Operation
Oil Pressure Switch	OPS2 Electronic Switch
Oil Control System	ALCO Trax-Oil OM3

MOTOR OPTIONS

<i>Motor Code</i>	<i>Power Supply</i>	<i>Nominal Voltage, V</i>	<i>Start Connection</i>	<i>DOL Connection</i>	<i>Amps Factor</i>
AWM	380-420 V / 3~ / 50 Hz	400	YYY	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
EWY	500-550 V / 3~ / 50 Hz	525	Y/DELTA	DELTA	0.76
AWR	220-240 V / 3~ / 50 Hz	230	YYY	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YYY	Y	0.76
TWY	500-550 V / 3~ / 50 Hz	525		DELTA	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YYY	Y	2.19
AWX	380 V / 3~ / 60 Hz	380	YYY	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YYY	Y	1.00