



Minimum Evaporating Temp. With:

- 20 °C Suction Gas Return ASERCOM certified
- 0 °C Suction Gas Return
- Maximum Evaporating Temperature
- 25 °C Suction Gas Return
- 0 °C Suction Gas Return with add cooling

Suction Return Temperature 20.0°C

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW									
	-50.0	-45.0	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0
5.0			30.90	39.70	50.30	62.70	77.00			
10.0			29.00	37.60	47.70	59.60	73.30	88.90	106.50	126.50
15.0			27.20	35.30	45.10	56.40	69.40	84.30	101.00	120.00
20.0			25.20	33.10	42.30	53.10	65.50	79.60	95.60	113.50
25.0			23.20	30.70	39.50	49.70	61.50	74.80	89.90	107.00
30.0			21.30	28.40	36.70	46.30	57.30	69.90	84.20	100.00
35.0			19.30	26.00	33.80	42.80	53.10	64.90	78.20	93.20
40.0				23.60	30.90	39.30	48.90	59.90	72.30	86.20
45.0					28.00	35.70	44.60	54.70	66.20	79.10
50.0					25.10	32.20	40.30	49.60	60.10	71.90
55.0						28.60	36.00	44.40	53.90	64.70

Cond °C	Power, kW									
	-50.0	-45.0	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0
5.0			11.05	12.15	13.15	14.00	14.75			
10.0			11.55	12.85	14.05	15.10	16.05	16.75	17.30	17.55
15.0			12.05	13.55	14.95	16.20	17.35	18.30	19.05	19.60
20.0			12.55	14.20	15.80	17.30	18.65	19.85	20.90	21.60
25.0			12.95	14.85	16.65	18.35	19.95	21.40	22.60	23.70
30.0			13.35	15.40	17.45	19.40	21.20	22.90	24.40	25.70
35.0			13.65	15.95	18.20	20.40	22.40	24.40	26.20	27.80
40.0				16.40	18.85	21.30	23.60	25.80	27.90	29.80
45.0					19.50	22.20	24.80	27.20	29.60	31.70
50.0					20.00	23.00	25.80	28.60	31.20	33.70
55.0						23.70	26.80	29.90	32.80	35.50

Cond °C	Current at 400 V, A									
	-50.0	-45.0	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0
5.0			26.01	27.26	28.40	29.39	30.18			
10.0			26.57	28.01	29.38	30.64	31.71	32.56	33.14	33.38
15.0			27.11	28.77	30.39	31.92	33.30	34.49	35.43	36.07
20.0			27.63	29.52	31.40	33.22	34.93	36.47	37.80	38.85
25.0			28.11	30.25	32.41	34.54	36.59	38.50	40.22	41.71
30.0			28.52	30.93	33.39	35.85	38.25	40.55	42.70	44.63
35.0			28.86	31.56	34.33	37.13	39.91	42.62	45.20	47.59
40.0				32.11	35.22	38.38	41.55	44.68	47.71	50.59
45.0					36.03	39.57	43.15	46.72	50.22	53.60
50.0					36.75	40.69	44.70	48.72	52.71	56.60
55.0						41.73	46.18	50.67	55.16	59.59

Cond °C	Suction Mass Flow, g/s									
	-50.0	-45.0	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0
5.0			165.50	213.00	271.00	339.00	418.00			
10.0			161.50	210.00	267.00	335.00	414.00	505.00	610.00	729.00
15.0			157.50	206.00	263.00	331.00	409.00	500.00	604.00	723.00
20.0			153.00	201.00	258.00	325.00	404.00	494.00	598.00	716.00
25.0			147.50	196.00	253.00	320.00	397.00	487.00	590.00	708.00
30.0			142.00	190.00	247.00	313.00	390.00	479.00	581.00	699.00
35.0			136.00	184.00	240.00	306.00	382.00	470.00	572.00	689.00
40.0				177.50	233.00	298.00	374.00	461.00	562.00	678.00
45.0					226.00	290.00	365.00	451.00	551.00	667.00
50.0					218.00	281.00	355.00	441.00	540.00	655.00
55.0						273.00	346.00	431.00	530.00	645.00

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Number of cylinders	6
Displacement @ 50 Hz, m <sup>3</sup> /h	127
Bore/Stroke, mm	74.7/55.6
Length/Width, mm	740/580
Height, mm	700
Net Weight, kg	261
Gross Weight, kg	277
Rotalock Discharge, inch	1 3/8
Suction, inch	2 1/8
Drive Frequency Range, Hz	25 - 60
Oil Quantity, l	6.8
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
Sound Pressure @ 1m (LT), dBA	81
Sound Power (LT), dBA	92
Sound Conditions (LT, Temperatures: Evap./Cond./Suction at freq./speed)	-35 / 40 / 20 °C at 50 Hz
Sound Pressure @ 1m (MT), dBA	74
Sound Power (MT), dBA	85
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10 / 45 / 20 °C at 50 Hz
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	3922
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	62.2
Locked Rotor Current, A	255
Default Enclosure Class	IP 54 (IEC 34)

**ACCESSORIES INCLUDED**

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Deep Oil Sump	Mounted

**ACCESSORIES OPTIONAL**

Enclosure Class	IP 56
Adapter Kit	For Parallel Operation
Capacity Control	Capacity Steps 66%
Crankcase Heater	200 W Internal
Check Valve	For unloaded start operation
Oil Pressure Switch	OPS2 Electronic Switch
Oil Control System	ALCO Trax-Oil OM3
Additional Cooling	70 W Vertical Air Flow Fan
Unloaded start	Available

**MOTOR OPTIONS**

<b>Motor Code</b>	<b>Power Supply</b>	<b>Nominal Voltage, V</b>	<b>Start Connection</b>	<b>DOL Connection</b>	<b>Amps Factor</b>
AWM	380-420 V / 3~ / 50 Hz	400	YYY	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
AWR	220-240 V / 3~ / 50 Hz	230	YYY	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YYY	Y	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YYY	Y	2.19
AWX	380 V / 3~ / 60 Hz	380	YYY	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YYY	Y	1.00