



Minimum Evaporating Temp. With:

█ 10 K Suction Superheat

█ Maximum Evaporating Temperature

Suction Superheat 10.0K

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW								
	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
21.0	17.90	22.40	27.90	34.40	42.30	45.90			
25.0	17.25	21.60	26.80	33.10	40.70	44.10	49.60		
30.0	16.40	20.70	25.70	31.60	38.70	41.90	47.20	52.00	
35.0	15.55	19.70	24.50	30.10	36.90	39.90	44.90	49.40	54.30
40.0	14.60	18.65	23.30	28.70	35.00	37.90	42.60	46.90	51.50
45.0	13.55	17.50	22.00	27.20	33.20	35.90	40.30	44.40	48.80
50.0		16.30	20.60	25.60	31.30	33.90	38.10	41.90	46.10
55.0		14.90	19.15	23.90	29.40	31.90	35.80	39.40	43.30
60.0			17.50	22.10	27.40	29.70	33.50	36.90	40.50
65.0			15.70	20.20	25.20	27.40	31.00	34.20	37.70
70.0				18.00	22.90	25.00	28.30	31.40	34.70
74.1				16.10	20.80	22.80	26.10	29.00	32.10

50 Hz

ZRT216KCE-TFD

R134a

Cond °C	Power, kW								
	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
21.0	5.12	5.18	5.24	5.32	5.43	5.49			
25.0	5.54	5.60	5.66	5.72	5.81	5.86	5.95		
30.0	6.09	6.17	6.23	6.28	6.35	6.39	6.45	6.52	
35.0	6.70	6.80	6.87	6.92	6.97	7.00	7.05	7.10	7.16
40.0	7.38	7.51	7.59	7.64	7.69	7.70	7.74	7.78	7.82
45.0	8.12	8.29	8.39	8.45	8.49	8.51	8.53	8.56	8.59
50.0		9.15	9.28	9.36	9.40	9.42	9.43	9.45	9.47
55.0		10.10	10.25	10.35	10.40	10.45	10.45	10.45	10.45
60.0			11.35	11.50	11.55	11.55	11.60	11.60	11.60
65.0			12.55	12.70	12.80	12.80	12.85	12.85	12.85
70.0				14.05	14.20	14.20	14.25	14.25	14.25
74.1				15.25	15.40	15.45	15.50	15.50	15.50

Cond °C	Current at 400 V, A								
	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
21.0	16.37	16.46	16.59	16.79	17.10	17.26			
25.0	16.50	16.56	16.65	16.79	17.01	17.13	17.35		
30.0	16.78	16.85	16.90	16.98	17.12	17.20	17.35	17.51	
35.0	17.22	17.29	17.34	17.38	17.46	17.50	17.60	17.70	17.84
40.0	17.79	17.90	17.95	17.98	18.01	18.04	18.09	18.15	18.23
45.0	18.49	18.65	18.74	18.77	18.78	18.79	18.81	18.84	18.88
50.0		19.55	19.68	19.74	19.75	19.75	19.75	19.76	19.78
55.0		20.57	20.78	20.88	20.92	20.92	20.92	20.91	20.91
60.0			22.02	22.19	22.27	22.28	22.28	22.28	22.26
65.0			23.40	23.66	23.80	23.83	23.85	23.85	23.84
70.0				25.28	25.50	25.56	25.61	25.63	25.64
74.1				26.71	27.02	27.10	27.19	27.23	27.26

Cond °C	Suction Mass Flow, g/s								
	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
21.0	106.00	130.50	159.00	193.00	233.00	251.00			
25.0	106.00	130.00	158.50	192.00	231.00	249.00	278.00		
30.0	105.50	130.00	158.50	191.00	230.00	247.00	275.00	300.00	
35.0	105.00	130.00	158.00	191.00	229.00	246.00	273.00	298.00	325.00
40.0	104.00	129.50	158.00	190.50	228.00	245.00	272.00	296.00	322.00
45.0	101.50	128.50	157.50	190.00	227.00	244.00	271.00	295.00	321.00
50.0		126.50	156.50	189.50	227.00	243.00	270.00	293.00	319.00
55.0		123.50	154.50	188.00	226.00	242.00	268.00	292.00	317.00
60.0			151.00	186.00	224.00	240.00	267.00	290.00	315.00
65.0			145.50	182.00	221.00	238.00	264.00	288.00	313.00
70.0				176.00	217.00	234.00	261.00	285.00	310.00
74.1				169.50	212.00	229.00	257.00	282.00	307.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m ³ /h	51.4
Length/Width, mm	635/312
Height, mm	577
Net Weight, kg	128
Gross Weight, kg	138
Stub Suction, inch	1 5/8
Stub Discharge, inch	1 3/8
Oil Quantity, l	6.51
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	546 x 190.5 (22.4)
Sound Pressure @ 1m (HT), dBA	63
Sound Power (HT), dBA	74
Sound Conditions (HT, Temperatures:	7 / 54 / 18 °C at 50 Hz
Evap./Cond./Suction at freq./speed)	
High Side PS gauge, bar	32
Low Side PS gauge, bar	20
Low Side TS Max., °C	52
Low Side TS Min., °C	-35
Refrigerant's GWP	1430
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	2 x 16.8
Locked Rotor Current, A	2 x 111
Default Enclosure Class	IP 21 (IEC 34)

ACCESSORIES INCLUDED

Enclosure Class	IP21
Oil Charge	
Discharge Temperature Protection	ASTP Therm-O-Disc In Scroll
Mounting Grommets	Rubber Grommet For Single
Oil Service Valve	Schraeder Valve
Check Valve	Discharge Low Leak Check Valve

ACCESSORIES OPTIONAL

Mounting Grommets	Hard Mounts for Paralleling
Sound Attenuation	Sound Shell (12dBA)
Adapter Kit	R1"1/4 -B 1"1/8 For TPTL for
Oil Control System	Parallel Operation
Crankcase Heater	ALCO Trax-Oil OM3
Enclosure Class	90 W External IP66 With Molded Plug

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
TFD	380-420 V / 3~ / 50 Hz	400		Y	1.00
TF5	200-220 V / 3~ / 50 Hz	200		Y	2.09
TFD	460 V / 3~ / 60 Hz	460		Y	1.04
TF5	200-230 V / 3~ / 60 Hz	230		Y	2.09