



Minimum Evaporating Temp. With:

- 25 °C Suction Gas Return
- 10 K Suction Superheat
- Maximum Evaporating Temperature

Suction Superheat 10.0K

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
27.0	21.30	27.90	35.60	44.40	54.40	65.40	70.10	77.50	84.00
30.0	20.50	27.10	34.90	43.70	53.60	64.60	69.30	76.70	83.20
35.0	19.20	25.70	33.40	42.10	51.90	62.80	67.50	74.80	81.30
40.0	17.80	24.20	31.70	40.20	49.90	60.60	65.20	72.40	78.70
45.0		22.60	29.80	38.10	47.40	57.90	62.40	69.40	75.60
50.0			27.80	35.80	44.80	54.90	59.20	66.00	72.00
55.0				33.30	41.90	51.50	55.70	62.20	68.00
60.0					38.90	48.00	51.90	58.20	63.60
65.0					35.80	44.30	48.00	53.80	59.00

50 Hz

ZRT250KC-TFD

R22

Cond °C	Power, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
27.0	9.29	9.32	9.32	9.36	9.49	9.79	9.96	10.30	10.65
30.0	10.00	10.05	10.05	10.10	10.20	10.45	10.65	10.95	11.25
35.0	11.25	11.35	11.40	11.40	11.50	11.70	11.80	12.10	12.35
40.0	12.65	12.75	12.80	12.85	12.90	13.05	13.15	13.35	13.60
45.0		14.35	14.40	14.40	14.45	14.55	14.60	14.80	15.00
50.0			16.15	16.20	16.20	16.25	16.30	16.40	16.55
55.0				18.15	18.15	18.15	18.20	18.25	18.35
60.0					20.30	20.30	20.30	20.30	20.40
65.0					22.80	22.70	22.70	22.70	22.70

Cond °C	Current at 400 V, A								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
27.0	23.78	23.92	24.10	24.32	24.59	24.90	25.03	25.25	25.44
30.0	24.36	24.51	24.69	24.90	25.15	25.43	25.55	25.75	25.91
35.0	25.48	25.64	25.82	26.02	26.24	26.48	26.58	26.73	26.87
40.0	26.84	27.01	27.19	27.37	27.57	27.76	27.84	27.96	28.06
45.0		28.67	28.85	29.03	29.19	29.35	29.41	29.49	29.56
50.0			30.87	31.03	31.17	31.29	31.33	31.38	31.41
55.0				33.45	33.56	33.64	33.65	33.67	33.67
60.0					36.41	36.45	36.45	36.43	36.40
65.0					39.79	39.79	39.77	39.72	39.66

Cond °C	Suction Mass Flow, g/s								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
27.0	124.00	160.50	203.00	250.00	302.00	359.00	384.00	421.00	454.00
30.0	122.50	160.00	203.00	251.00	304.00	363.00	387.00	426.00	459.00
35.0	119.00	157.50	202.00	251.00	306.00	366.00	391.00	431.00	465.00
40.0	115.00	154.00	199.00	249.00	305.00	367.00	393.00	433.00	468.00
45.0		150.50	195.50	246.00	303.00	365.00	392.00	433.00	468.00
50.0			191.00	242.00	299.00	362.00	388.00	430.00	466.00
55.0				237.00	294.00	356.00	383.00	425.00	461.00
60.0					287.00	349.00	376.00	417.00	454.00
65.0					280.00	341.00	367.00	408.00	444.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m³/h	57.6
Length/Width, mm	635/312
Height, mm	577
Net Weight, kg	129
Gross Weight, kg	141
Stub Suction, inch	1 5/8
Stub Discharge, inch	1 3/8
Oil Quantity, l	6.51
Oil type (original charge)	Suniso 3GS
Oil type (approved oils)	Suniso 3GS
Base mounting (hole dia), mm	745 x 220 (22.6)
High Side PS gauge, bar	32
Low Side PS gauge, bar	20
Low Side TS Max., °C	52
Low Side TS Min., °C	-35
Refrigerant's GWP	1810
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	2 x 19.6
Locked Rotor Current, A	2 x 118
Default Enclosure Class	IP 21 (IEC 34)

ACCESSORIES INCLUDED

Mounting Grommets	Rubber Grommet For Single
Oil Service Valve	Schraeder Valve
Check Valve	Discharge Low Leak Check Valve
Discharge Temperature Protection	ASTP Therm-O-Disc In Scroll
Enclosure Class	IP21
Oil Charge	

ACCESSORIES OPTIONAL

Crankcase Heater	90 W External
Enclosure Class	IP66 With Molded Plug
Adapter Kit	R1"1/4 -B 1"1/8 For TPTL for
Oil Control System	Parallel Operation
Mounting Grommets	ALCO Trax-Oil OM3
Sound Attenuation	Hard Mounts for Paralleling Sound Shell (12dBA)

50 Hz

ZRT250KC-TFD

R22

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
TFD	380-420 V / 3~ / 50 Hz	400		Y	1.00