

Invotech Selection Software

REFRIGERANT R404A

Operation Conditions

Evaporating Temperature(ℓ): -10,0

Condensing Temperature(ℓ): 45,0

Liquid subcooling: 0,0

Suction Superheat: 30,0

Required Capacity(Kw):

Compressor Selected: YF17E1G-Q100

PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW) 4,11

Power Input (KW) 2,09

COP 1,97

Current (A) 3,97

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm) 239/239/418

Weight (kg) 29

Stub Suction (inch) 7/8

Stub Discharge (inch) 1/2

Base mounting (hole dia) 190X190(8.5)

Oil type POE

Initial charge of oil quantity (L) 1.4

Recharge of oil quantity (L) 1.25

High Side PS Max., (MPa) 3.2

Low Side PS Max., (MPa) 2.0

Displacement(m³/h) 7.3

COMPRESSOR ELECTRICAL DATA

Electricity 380V/50Hz/3P

Standard Conditions -31.6/40.6/36/0

Normal Power (HP) 2.5

Normal Capacity (ℓ) 1770

Normal Power input(ℓ) 1567

Normal COP(ℓ/ℓ) 1.13

Normal Current(ℓ) 2.9

Locked Rotor Current(ℓ) 22

Maximum operating current(ℓ) 4.4

Model: YF17E1G-Q100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

Capacity(KW)

Tc\Te	-40	-35	-30	-25	-20	-15	-10	-5	0	
25	1,55	1,94	2,41	2,98	3,66	4,43	5,31	6,31	7,43	
30	1,48	1,85	2,3	2,85	3,49	4,22	5,06	6,01	7,07	
35	1,39	1,74	2,17	2,69	3,29	3,98	4,77	5,67	6,67	
40	1,29	1,62	2,03	2,51	3,07	3,71	4,45	5,29	6,22	
45	1,2	1,5	1,87	2,31	2,83	3,43	4,11	4,88	5,75	
50	1,11	1,38	1,72	2,12	2,58	3,13	3,75	4,46	5,26	
55	1,03	1,27	1,56	1,92	2,34	2,82	3,38	4,02	4,74	
60					2,1	2,52	3,01	3,58	4,22	

Power Input(KW)

Tc\Te	-40	-35	-30	-25	-20	-15	-10	-5	0	
25	1,08	1,14	1,21	1,28	1,35	1,43	1,5	1,59	1,67	
30	1,18	1,25	1,32	1,4	1,48	1,56	1,65	1,73	1,83	
35	1,28	1,36	1,44	1,52	1,61	1,69	1,78	1,88	1,97	
40	1,39	1,48	1,56	1,65	1,74	1,83	1,93	2,03	2,13	
45	1,53	1,62	1,71	1,8	1,89	1,99	2,09	2,19	2,3	
50	1,7	1,79	1,88	1,98	2,07	2,17	2,27	2,38	2,49	
55	1,91	2	2,1	2,19	2,29	2,4	2,5	2,61	2,72	
60					2,57	2,67	2,77	2,88	2,99	

Model: YF17E1G-Q100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

Current(A)

Tc\Te	-40	-35	-30	-25	-20	-15	-10	-5	0	
25	2,79	2,85	2,92	2,99	3,07	3,15	3,25	3,34	3,45	
30	2,89	2,97	3,04	3,13	3,22	3,32	3,42	3,53	3,65	
35	2,99	3,08	3,17	3,26	3,37	3,47	3,59	3,71	3,84	
40	3,11	3,2	3,3	3,41	3,52	3,64	3,77	3,9	4,04	
45	3,26	3,36	3,47	3,59	3,71	3,84	3,97	4,12	4,26	
50	3,46	3,57	3,69	3,82	3,95	4,08	4,23	4,38	4,53	
55	3,73	3,85	3,98	4,11	4,25	4,39	4,54	4,7	4,86	
60					4,63	4,78	4,94	5,1	5,27	

Mass Flow(Kg/h)

Tc\Te	-40	-35	-30	-25	-20	-15	-10	-5	0	
25	35,4	44,87	56,04	69,25	84,88	103,27	124,78	149,76	178,57	
30	35,51	44,94	56,09	69,3	84,95	103,38	124,95	150,01	178,93	
35	35,36	44,69	55,77	68,93	84,55	102,97	124,55	149,64	178,61	
40	35,07	44,26	55,21	68,28	83,81	102,17	123,71	148,78	177,75	
45	34,78	43,78	54,56	67,47	82,87	101,12	122,57	147,57	176,49	
50	34,63	43,39	53,94	66,65	81,87	99,95	121,26	146,14	174,96	
55	34,76	43,22	53,5	65,95	80,94	98,81	119,92	144,63	173,3	
60					80,21	97,82	118,69	143,18	171,64	