

## Invotech Selection Software

REFRIGERANT R410A

### Operation Conditions :

Evaporating Temperature (°C) : 5,0  
 Condensing Temperature (°C) : 50,0  
 Liquid subcooling: 0,0  
 Suction Superheat: 10,0

### Required Capacity(Kw):

Compressor Selected: YH880C1-100

### PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	80,71
Power Input (KW)	24,22
COP	3,33
Current (A)	42,54

### COMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	356.3/326.2/671.2
Weight (kg)	104
Stub Suction (inch)	1 5/8
Stub Discharge (inch)	1 1/8
Base mounting (hole dia)	232X232(11)
Oil type	POE
Initial charge of oil quantity (L)	5.5
Recharge of oil quantity (L)	5.3
High Side PS Max., (MPa)	4.3
Low Side PS Max., (MPa)	2.0
Displacement(m <sup>3</sup> /h)	57.9

### COMPRESSOR ELECTRICAL DATA

Electricity	380V/50Hz/3P
Standard Conditions	7.2/54.4/11.1/8.3
Normal Power (HP)	30
Normal Capacity (W)	88000
Normal Power input (W)	26800
Normal COP (W/W)	3.3
Normal Current ( A )	55
Locked Rotor Current ( A )	348
Maximum operating current ( A )	66

Model: YH880C1-100

Refrigerant: R410A

Suction Superheat: 10,0

Liquid subcooling: 0,0

**Capacity (KW)**

Tc \ Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	43,5	50,21	58,68	69,28	82,4	98,42	117,73			
30	36,29	42,93	51,07	61,1	73,4	88,35	106,33			
35	31,39	38,03	45,94	55,47	67,03	80,99	97,74	117,66	128,92	
40	27,99	34,73	42,47	51,6	62,5	75,55	91,14	109,65	120,12	
45		32,2	39,87	48,67	58,99	71,22	85,74	102,92	112,64	
50			37,32	45,87	55,7	67,19	80,71	96,66	105,66	
55				42,41	51,83	62,65	75,27	90,05	98,38	
60					46,56	56,81	68,59	82,3	90	
65						48,85	59,89	72,6	79,7	

**Power Input (KW)**

Tc \ Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	14,84	14,85	14,95	15,15	15,46	15,9	16,47			
30	15,67	15,73	15,84	16,01	16,25	16,58	17			
35	16,84	16,98	17,14	17,31	17,53	17,78	18,1	18,47	18,69	
40	18,29	18,55	18,79	19,02	19,23	19,46	19,7	19,96	20,11	
45		20,4	20,76	21,06	21,32	21,55	21,76	21,95	22,04	
50			22,98	23,4	23,75	24,02	24,22	24,38	24,44	
55				25,98	26,45	26,8	27,04	27,2	27,25	
60					29,37	29,84	30,17	30,37	30,42	
65						33,1	33,55	33,82	33,9	

Model: YH880C1-100  
 Suction Superheat: 10,0

Refrigerant: R410A  
 Liquid subcooling: 0,0

**Current (A)**

Tc \ Te	-25	-20	-15	-10	-5	0	5	10	12,5
25	28,32	28,57	28,85	29,16	29,52	29,93	30,39		
30	30,49	30,61	30,79	31,01	31,3	31,66	32,1		
35	32,97	32,96	33,02	33,16	33,38	33,69	34,1	34,61	34,9
40	35,84	35,7	35,64	35,68	35,83	36,08	36,45	36,94	37,24
45		38,89	38,72	38,66	38,72	38,91	39,24	39,71	40
50			42,33	42,16	42,13	42,26	42,54	42,98	43,27
55				46,27	46,15	46,2	46,43	46,84	47,12
60					50,84	50,81	50,98	51,36	51,62
65						56,18	56,28	56,61	56,86

**Mass Flow (Kg/h)**

Tc \ Te	-25	-20	-15	-10	-5	0	5	10	12,5
25	640,77	793,37	969,31	1171,79	1403,96	1669,01	1970,12		
30	633,26	785,66	961,46	1163,84	1395,99	1661,07	1962,26		
35	624,3	775,97	951,12	1152,9	1384,5	1649,1	1949,86	2289,98	2475,79
40	614,48	764,93	938,89	1139,56	1370,1	1633,69	1933,52	2272,75	2458,14
45		753,11	925,39	1124,42	1353,39	1615,47	1913,83	2251,67	2436,38
50			911,2	1108,09	1334,97	1595,01	1891,41	2227,32	2411,1
55				1091,16	1315,44	1572,94	1866,84	2200,33	2382,9
60					1295,4	1549,84	1840,73	2171,27	2352,4
65						1526,31	1813,69	2140,77	2320,19