

## Invotech Selection Software

REFRIGERANT R404A

### Operation Conditions :

Evaporating Temperature (°C) : -10,0

Condensing Temperature (°C) : 45,0

Liquid subcooling: 0,0

Suction Superheat: 30,0

### Required Capacity(Kw):

Compressor Selected: YM350E1G-100

#### PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	31,52
Power Input (KW)	15,39
COP	2,05
Current (A)	29,57

#### COMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	356.3/326.2/676.7
Weight (kg)	100
Stub Suction (inch)	1 5/8
Stub Discharge (inch)	1 1/4
Base mounting (hole dia)	232X232(11)
Oil type	POE
Initial charge of oil quantity (L)	5.5
Recharge of oil quantity (L)	5.3
High Side PS Max., (MPa)	3.2
Low Side PS Max., (MPa)	2.0
Displacement(m <sup>3</sup> /h)	57.9

#### COMPRESSOR ELECTRICAL DATA

Electricity	380V/50Hz/3P
Standard Conditions	-6.7/48.9/11.1/0
Normal Power (HP)	20
Normal Capacity (W)	33300
Normal Power input (W)	16650
Normal COP (W/W)	2
Normal Current ( A )	29.4
Locked Rotor Current ( A )	266
Maximum operating current ( A )	41

Model: YM350E1G-100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Capacity (KW)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	19,61	23,59	28,56	34,68	42,15					
15	19,23	23,33	28,34	34,43	41,81					
20	18,6	22,75	27,74	33,76	40,98	49,59				
25	17,76	21,91	26,83	32,71	39,72	48,06	57,91			
30	16,78	20,87	25,66	31,34	38,09	46,1	55,55	66,61	79,48	
35	15,71	19,68	24,29	29,71	36,14	43,76	52,75	63,29	75,57	
40	14,61	18,4	22,77	27,88	33,93	41,1	49,58	59,54	71,17	
45	13,53	17,09	21,15	25,9	31,52	38,18	46,09	55,41	66,33	
50	12,54	15,8	19,51	23,83	28,95	35,06	42,33	50,96	61,12	
55	11,68	14,6	17,88	21,72	26,29	31,78	38,37	46,24	55,58	
60			16,34	19,64	23,6	28,41	34,26	41,32	49,78	
65				17,63	20,93	25,01	30,05	36,25	43,77	

**Power Input (KW)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	6,61	6,95	7,23	7,48	7,69					
15	7,53	7,97	8,35	8,69	9					
20	8,32	8,86	9,35	9,79	10,18	10,54				
25	9,02	9,67	10,26	10,8	11,28	11,72	12,13			
30	9,66	10,42	11,11	11,75	12,32	12,85	13,34	13,78	14,2	
35	10,27	11,13	11,93	12,66	13,34	13,95	14,52	15,05	15,53	
40	10,87	11,85	12,75	13,58	14,35	15,06	15,71	16,32	16,88	
45	11,5	12,59	13,6	14,53	15,39	16,19	16,93	17,62	18,25	
50	12,19	13,39	14,5	15,53	16,49	17,38	18,21	18,98	19,69	
55	12,96	14,27	15,49	16,63	17,69	18,67	19,58	20,43	21,22	
60			16,6	17,84	19	20,07	21,08	22,01	22,88	
65				19,2	20,46	21,63	22,72	23,74	24,69	

Model: YM350E1G-100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Current (A)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10
10	18,04	17,93	18	18,33	19				
15	19,07	18,93	18,91	19,11	19,6				
20	20,26	20,12	20,05	20,15	20,48	21,13			
25	21,63	21,51	21,43	21,46	21,67	22,15	22,97		
30	23,17	23,11	23,05	23,04	23,17	23,51	24,14	25,14	26,58
35	24,89	24,94	24,91	24,9	24,97	25,21	25,69	26,48	27,67
40	26,81	26,98	27,04	27,05	27,1	27,27	27,62	28,24	29,21
45	28,94	29,27	29,43	29,5	29,57	29,69	29,95	30,44	31,21
50	31,27	31,79	32,1	32,26	32,36	32,48	32,69	33,06	33,68
55	33,81	34,56	35,04	35,33	35,51	35,65	35,83	36,13	36,62
60			38,28	38,72	39,01	39,2	39,39	39,64	40,04
65				42,44	42,86	43,15	43,37	43,62	43,95

**Mass Flow (Kg/h)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10
10	446,3	564,06	696,74	849,88	1028,99				
15	449,98	564,95	695,46	847,03	1025,19				
20	450,2	562,32	690,59	840,54	1017,68	1227,56			
25	447,7	556,9	682,87	831,13	1007,21	1216,62	1464,9		
30	443,2	549,43	673,04	819,55	994,49	1203,39	1451,76	1745,13	2089,02
35	437,44	540,64	661,83	806,53	980,28	1188,59	1436,99	1731	2076,15
40	431,16	531,26	649,97	792,81	965,29	1172,96	1421,32	1715,92	2062,26
45	425,09	522,04	638,2	779,11	950,28	1157,23	1405,51	1700,62	2048,09
50	419,96	513,69	627,25	766,17	935,96	1142,15	1390,27	1685,84	2034,38
55	416,52	506,97	617,87	754,73	923,08	1128,44	1376,34	1672,31	2021,86
60			610,77	745,52	912,36	1116,84	1364,47	1660,77	2011,27
65				739,27	904,55	1108,08	1355,37	1651,95	2003,34