

## Invotech Selection Software

REFRIGERANT

R404A

### Operation Conditions :

Evaporating Temperature (°C) : -10,0

Condensing Temperature (°C) : 45,0

Liquid subcooling: 0,0

Suction Superheat: 30,0

### Required Capacity(Kw):

Compressor Selected:

YM43E1G-100

### PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW) 4,43

Power Input (KW) 2,11

COP 2,1

Current (A) 3,87

### CPMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm) 239/239/418

Weight (kg) 30

Stub Suction (inch) 7/8

Stub Discharge (inch) 1/2

Base mounting (hole dia) 190X190(8.5)

Oil type POE

Initial charge of oil quantity (L) 1.4

Recharge of oil quantity (L) 1.25

High Side PS Max., (MPa) 3.2

Low Side PS Max., (MPa) 2.0

Displacement(m³/h) 7.3

### COMPRESSOR ELECTRICAL DATA

Electricity 380V/50Hz/3P

Standard Conditions -6.7/48.9/11.1/0

Normal Power (HP) 2.5

Normal Capacity (W) 4250

Normal Power input (W) 2297

Normal COP (W/W) 1.85

Normal Current ( A ) 4.8

Locked Rotor Current ( A ) 45

Maximum operating current ( A ) 6.4

Model: YM43E1G-100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Capacity (KW)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10	
10	3,11	3,78	4,61	5,62	6,82					
15	2,9	3,56	4,35	5,3	6,44					
20	2,73	3,36	4,11	5,02	6,09	7,35				
25	2,57	3,18	3,89	4,74	5,75	6,93	8,3			
30	2,43	3,01	3,68	4,48	5,43	6,53	7,81	9,29	10,98	
35	2,29	2,84	3,48	4,23	5,1	6,13	7,32	8,69	10,27	
40	2,14	2,66	3,27	3,96	4,78	5,72	6,82	8,09	9,54	
45		2,48	3,04	3,69	4,43	5,3	6,31	7,47	8,81	
50			2,8	3,39	4,07	4,86	5,77	6,83	8,05	
55				3,06	3,68	4,39	5,21	6,16	7,26	
60					3,25	3,88	4,61	5,46	6,44	
65						3,33	3,97	4,71	5,57	

**Power Input (KW)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10	
10	0,97	1,01	1,06	1,12	1,19					
15	1,05	1,09	1,15	1,21	1,28					
20	1,13	1,19	1,25	1,31	1,38	1,45				
25	1,23	1,29	1,36	1,43	1,5	1,57	1,65			
30	1,34	1,4	1,48	1,55	1,63	1,7	1,78	1,85	1,92	
35	1,45	1,53	1,61	1,69	1,77	1,85	1,93	2	2,07	
40	1,58	1,67	1,76	1,84	1,93	2,01	2,09	2,17	2,24	
45		1,82	1,92	2,01	2,11	2,19	2,28	2,36	2,43	
50			2,1	2,2	2,3	2,39	2,48	2,56	2,64	
55				2,4	2,51	2,61	2,71	2,79	2,87	
60					2,74	2,85	2,95	3,04	3,12	
65						3,11	3,22	3,32	3,4	

Model: YM43E1G-100

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Current (A)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10	
10	2,52	2,56	2,61	2,67	2,75					
15	2,59	2,64	2,7	2,77	2,84					
20	2,68	2,74	2,8	2,88	2,96	3,05				
25	2,78	2,85	2,92	3,01	3,09	3,18	3,28			
30	2,9	2,98	3,06	3,15	3,25	3,35	3,45	3,54	3,64	
35	3,03	3,12	3,22	3,33	3,43	3,53	3,64	3,74	3,84	
40	3,18	3,29	3,41	3,52	3,64	3,75	3,86	3,97	4,07	
45		3,49	3,62	3,75	3,87	3,99	4,11	4,23	4,33	
50			3,86	4	4,14	4,27	4,4	4,52	4,63	
55				4,28	4,44	4,58	4,72	4,85	4,97	
60					4,77	4,94	5,09	5,23	5,36	
65						5,32	5,49	5,64	5,78	

**Mass Flow (Kg/h)**

T <sub>c</sub> \ T <sub>e</sub>	-30	-25	-20	-15	-10	-5	0	5	10	
10	61,2	76,49	94,25	115,27	140,32					
15	60,02	75,12	92,66	113,44	138,25					
20	59,16	74,09	91,44	112,01	136,59	165,97				
25	58,51	73,3	90,49	110,89	135,26	164,42	199,15			
30	57,99	72,66	89,72	109,96	134,17	163,14	197,66	238,52	286,52	
35	57,49	72,08	89,03	109,15	133,21	162,02	196,36	237,02	284,8	
40	56,93	71,45	88,33	108,34	132,29	160,96	195,15	235,65	283,24	
45		70,69	87,52	107,46	131,32	159,89	193,95	234,3	281,72	
50			86,5	106,4	130,2	158,69	192,65	232,88	280,17	
55				105,07	128,84	157,27	191,16	231,3	278,49	
60					127,14	155,54	189,39	229,47	276,57	
65						153,41	187,24	227,29	274,34	