

## Invotech Selection Software

REFRIGERANT R404A

### Operation Conditions :

Evaporating Temperature (°C) : -10,0

Condensing Temperature (°C) : 45,0

Liquid subcooling: 0,0

Suction Superheat: 30,0

### Required Capacity(Kw):

Compressor Selected: YM43E2G-102

#### PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	4,43
Power Input (KW)	2,22
COP	2
Current (A)	10,08

#### COMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	239/239/418
Weight (kg)	31
Stub Suction (inch)	7/8
Stub Discharge (inch)	1/2
Base mounting (hole dia)	190X190(8.5)
Oil type	POE
Initial charge of oil quantity (L)	1.4
Recharge of oil quantity (L)	1.25
High Side PS Max., (MPa)	3.2
Low Side PS Max., (MPa)	2.0
Displacement(m <sup>3</sup> /h)	7.3

#### COMPRESSOR ELECTRICAL DATA

Electricity	220V/50Hz/1P
Standard Conditions	-6.7/48.9/11.1/0
Normal Power (HP)	2.5
Normal Capacity (W)	4250
Normal Power input (W)	2361
Normal COP (W/W)	1.76
Normal Current ( A )	11.2
Locked Rotor Current ( A )	76
Maximum operating current ( A )	17.2

Model: YM43E2G-102

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Capacity (KW)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	3,11	3,78	4,61	5,62	6,82					
15	2,9	3,56	4,35	5,3	6,44					
20	2,73	3,36	4,11	5,02	6,09	7,35				
25	2,57	3,18	3,89	4,74	5,75	6,93	8,3			
30	2,43	3,01	3,68	4,48	5,43	6,53	7,81	9,29	10,98	
35	2,29	2,84	3,48	4,23	5,1	6,13	7,32	8,69	10,27	
40	2,14	2,66	3,27	3,96	4,78	5,72	6,82	8,09	9,54	
45		2,48	3,04	3,69	4,43	5,3	6,31	7,47	8,81	
50			2,8	3,39	4,07	4,86	5,77	6,83	8,05	
55				3,06	3,68	4,39	5,21	6,16	7,26	
60					3,25	3,88	4,61	5,46	6,44	
65						3,33	3,97	4,71	5,57	

**Power Input (KW)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	1,07	1,11	1,16	1,22	1,29					
15	1,15	1,2	1,25	1,32	1,38					
20	1,24	1,29	1,35	1,42	1,49	1,56				
25	1,33	1,4	1,46	1,53	1,6	1,68	1,75			
30	1,44	1,51	1,58	1,66	1,74	1,81	1,89	1,96	2,04	
35	1,56	1,64	1,72	1,8	1,88	1,96	2,04	2,11	2,19	
40	1,69	1,78	1,87	1,95	2,04	2,12	2,21	2,28	2,35	
45		1,93	2,03	2,13	2,22	2,31	2,39	2,47	2,54	
50			2,21	2,31	2,41	2,51	2,6	2,68	2,76	
55				2,52	2,63	2,73	2,82	2,91	2,99	
60					2,86	2,97	3,07	3,16	3,25	
65						3,23	3,34	3,44	3,53	

Model: YM43E2G-102

Refrigerant: R404A

Suction Superheat: 30,0

Liquid subcooling: 0,0

**Current (A)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10
10	5,45	5,57	5,73	5,95	6,21				
15	5,68	5,83	6,03	6,26	6,52				
20	5,97	6,16	6,38	6,64	6,92	7,22			
25	6,31	6,55	6,81	7,09	7,39	7,7	8,04		
30	6,72	7,01	7,3	7,61	7,93	8,26	8,6	8,95	9,3
35	7,2	7,53	7,87	8,22	8,56	8,91	9,26	9,61	9,95
40	7,74	8,13	8,52	8,9	9,28	9,65	10,01	10,36	10,7
45		8,81	9,25	9,67	10,08	10,47	10,85	11,21	11,56
50			10,05	10,52	10,97	11,4	11,8	12,17	12,52
55				11,47	11,96	12,42	12,84	13,23	13,59
60					13,04	13,54	13,99	14,41	14,77
65						14,76	15,25	15,69	16,08

**Mass Flow (Kg/h)**

Tc \ Te	-30	-25	-20	-15	-10	-5	0	5	10
10	61,2	76,49	94,25	115,27	140,32				
15	60,02	75,12	92,66	113,44	138,25				
20	59,16	74,09	91,44	112,01	136,59	165,97			
25	58,51	73,3	90,49	110,89	135,26	164,42	199,15		
30	57,99	72,66	89,72	109,96	134,17	163,14	197,66	238,52	286,52
35	57,49	72,08	89,03	109,15	133,21	162,02	196,36	237,02	284,8
40	56,93	71,45	88,33	108,34	132,29	160,96	195,15	235,65	283,24
45		70,69	87,52	107,46	131,32	159,89	193,95	234,3	281,72
50			86,5	106,4	130,2	158,69	192,65	232,88	280,17
55				105,07	128,84	157,27	191,16	231,3	278,49
60					127,14	155,54	189,39	229,47	276,57
65						153,41	187,24	227,29	274,34