



**Dimensions**

A (mm) :	2407	B (mm) :	690	C (mm) :	645	F (mm) :	495	E1 (mm) :	718
E2 (mm) :	700	E (mm) :	2135	#REF! :	Ø22	#REF! :	Ø54	W (kg) :	164

**Capacity Information**

Capacity	30,705.00 Watt	Heat Transfer Surface	115,1 m <sup>2</sup>
Average Room Temperature	0.00 °C	Tube Volume	34,3 dm <sup>3</sup>
Evaporasyon Sıcaklığı	-8.00 °C	Fin Spacing	6 mm
ΔT	8 K	Test Pressure / Max. Operating Pressure	35 /25 bar
Refrigerant	R404A	Energy Efficiency Class	D
Altitude	0 m	Air Throw Distance	15.3 m

**Evaporator Fan Data**

Air Flow	13961 m <sup>3</sup> /h	Fan Protection / Isolation Class	IP54 / CLASS F
Number of Fans / Fan Diameter / Fan Cycle	3 / 450 mm / 1310 rpm	Operating Temperature Range	-40/60
Total Fan Power / Current	1.47 kW / 7.08 A	Sound Power Level (LWA)	80 dBA
Fan Voltage / Fan Frequency / Fan Phase	230 Volt / 50 Hz / 1 Ph	Sound Pressure Level (LPA)	58 dBA @ 3 m
fan rankings	1x3		

**Configuration**

**Configuration Name**

**Code**

Cassette Type	RAL 9016 painted Galvanized Sheet	-
Defrost Type	E2 Defrost (Coil + Tray)	6x2260+2x2260 Watt

**Notes.**

- Capacity correction calculation for altitude is according to related Eurovent Standard.
- Sound pressure calculation standard: EN13487
- Energy Efficiency Class calculation standards: EN328 and Related Eurovent Standard. Standard Conditions: SC2,R404A
- All of the technical information is subject to change without notice.
- All of the performance and technical data according to default configuration.

**Karyer Isı Transfer Sanayi ve Ticaret A.Ş.**

Topçular Mah. Tikveşli Yolu No:8 34140 Topçular - Eyüp / İstanbul Tel: 0 (212) 567 55 09 Pbx

Faks: 0 (212) 576 23 45

E-mail: info@karyergroup.com Web: http://www.karyergroup.com/