



Dimensions

A (mm) :	2907	B (mm) :	730	C (mm) :	530	F (mm) :	560	E1 (mm) :	518
E2 (mm) :	500	E (mm) :	2535	#REF! :	Ø22	#REF! :	Ø28	W (kg) :	159

Capacity Information

Capacity	17,701.00 Watt	Heat Transfer Surface	63,3 m ²
Average Room Temperature	0.00 °C	Tube Volume	23,7 dm ³
Evaporasyon Sıcaklığı	-8.00 °C	Fin Spacing	7 mm
ΔT	8 K	Test Pressure / Max. Operating Pressure	35 / 25 bar
Refrigerant	R404A	Energy Efficiency Class	E
Altitude	0 m	Air Throw Distance	14.0 m

Evaporator Fan Data

Air Flow	11250 m ³ /h	Fan Protection / Isolation Class	IP44 / CLASS F
Number of Fans / Fan Diameter / Fan Cycle	5 / 350 mm / 1340 rpm	Operating Temperature Range	-25/65
Total Fan Power / Current	0.825 kW / 3.65 A	Sound Power Level (LWA)	77 dBA
Fan Voltage / Fan Frequency / Fan Phase	230 Volt / 50 Hz / 1 Ph	Sound Pressure Level (LPA)	55 dBA @ 3 m
fan rankings	1x5		

Configuration

Configuration Name

Code

Cassette Type	RAL 9016 painted Galvanized Sheet	-
Defrost Type	E2 Defrost (Coil + Tray)	2x2600+1x2600 Watt

Notes.

- Capacity correction calculation for altitude is according to related Eurovent Standard.
- Sound pressure calculation standard: EN13487
- All of the technical information is subject to change without notice.
- All of the performance and technical data according to default configuration.

Karyer Isı Transfer Sanayi ve Ticaret A.Ş.

Topçular Mah. Tikveşli Yolu No:8 34140 Topçular - Eyüp / İstanbul Tel: 0 (212) 567 55 09 Pbx

Faks: 0 (212) 576 23 45

E-mail: info@karyergroup.com Web: http://www.karyergroup.com/