


ED-630AC4-C25**Evaporator
Technical Specifications****Dimensions**

A (mm) :	3308	B (mm) :	1030	C (mm) :	245	F (mm) :	985	G (mm) :	305
E1 (mm) :	3035	E2 (mm) :	518	E3 (mm) :	500	#REF! :	Ø22	#REF! :	Ø28
W (kg) :	125								

Capacity Information

Capacity	24,129.81 Watt	Heat Transfer Surface	75,6 m ²
Average Room Temperature	10.00 °C	Tube Volume	14,6 dm ³
Evaporasyon Sıcaklığı	0.00 °C	Fin Spacing	4.2 mm
ΔT	10 K	Test Pressure / Max. Operating Pressure	35 /25 bar
Refrigerant	R404A	Energy Efficiency Class	D
Altitude	0 m	Air Throw Distance	2x9,1 m

Evaporator Fan Data

Air Flow	7578 m ³ /h	Fan Protection / Isolation Class	IP41 / CLASS B
Number of Fans / Fan Diameter / Fan Cycle	6 / 300 mm / 1300 rmp	Operating Temperature Range	-40/40
Total Fan Power / Current	0.72 kW / 5.22 A	Sound Power Level (LWA)	70 dBA
Fan Voltage / Fan Frequency / Fan Phase	230 Volt / 50 Hz / 1 Ph	Sound Pressure Level (LPA)	48 dBA @ 3 m
fan rankings	1x6		

Configuration**Configuration Name****Code**

Cassette Type	RAL 9016 painted Galvanized Sheet	-
Defrost Type	E1 Defrost (Coil)	2x3100+2x3100 Watt

Notes.

- Capacity correction calculation for altitude is according to related Eurovent Standard.
- Sound pressure calculation standard: EN13487
- Energy Efficiency Class calculation standards: EN328 and Related Eurovent Standard. Standard Conditions: SC2,R404A
- All of the technical information is subject to change without notice.
- All of the performance and technical data according to default configuration.

Karyer Isı Transfer Sanayi ve Ticaret A.Ş.

Topçular Mah. Tikveşli Yolu No:8 34140 Topçular - Eyüp / İstanbul Tel: 0 (212) 567 55 09 Pbx
Faks: 0 (212) 576 23 45
E-mail: info@karyergroup.com Web: http://www.karyergroup.com/