


## KC-WF-2x391BC1-C06C Δ

### Condenser Technical Specifications



#### Dimensions

A (mm) :	2530	B (mm) :	2300	C (mm) :	4100	E (mm) :	1000	#REF! :	4xØ42
#REF! :	4xØ35								

#### Capacity Information

Capacity	654,226.00 Watt	Heat Transfer Surface	1408,3 m <sup>2</sup>
Ambient Temperature	25.00 °C	Tube Volume	157 dm <sup>3</sup>
Condensation Temperature	40.00 °C	Fin Spacing	2.1 mm
ΔT	15 K	Test Pressure / Max. Operating Pressure	35 / 27 bar
Refrigerant	R404A	Energy Efficiency Class	D
Altitude	0 m		

#### Evaporator Fan Data

Air Flow	175060 m <sup>3</sup> /h	Fan Protection / Isolation Class	IP54 / CLASS F
Number of Fans / Fan Diameter / Fan Cycle	6 / 910 mm / 840 rpm	Operating Temperature Range	-40/70
Total Fan Power / Current	16.8 kW / 32.4 A	Sound Power Level (LWA)	98 dBA
Fan Voltage / Fan Frequency / Fan Phase	400 Volt / 50 Hz / 3 Ph	Sound Pressure Level (LPA)	86 dBA @ 1 m
fan rankings	2x3		

Configuration	Configuration Name	Code
Cassette Type	RAL 9016 painted Galvanized Sheet	-

#### Notes.

- Capacity correction calculation for altitude is according to related Eurovent Standard.
- Sound pressure calculation standard: EN13487
- Energy Efficiency Class calculation standards: EN327 and Related Eurovent Standard. Standard Conditions: Tair inlet=25 °C, Tcond.= 40 °C, R404A, P= 1,01325 bar.
- All of the technical information is subject to change without notice.
- All of the performance and technical data according to default configuration.

#### Karyer Isı Transfer Sanayi ve Ticaret A.Ş.

Topçular Mah. Tikveşli Yolu No:8 34140 Topçular - Eyüp / İstanbul Tel: 0 (212) 567 55 09 Pbx  
Faks: 0 (212) 576 23 45  
E-mail: info@karyergroup.com Web: <http://www.karyergroup.com/>