

System : English Refrigerant : R22 Series Family : A
Compressor Model : H23A623DBE Revision : 0 BOM ID : -

Techninal Specifications

Voltage	Phase	Frequency
415-380	3	50

Application	H	Evaporator temperature Range	-20 °F to 55 °F
-------------	---	------------------------------	-----------------

Nominal Performance Data @50Hz

Performance	ARI	ASRET	13 SEER B	ARI (45/100)	HEATPUMP
	460	460	460	460	460
Capacity (Btu/hr.)	67000	60800	86600	78200	50200
Motor Input (Watt)	5230	5050	4190	4160	3970
Current (Amp)	8.51	8.25	7.11	7.08	6.83
EER (Btu/W-hr.)	10.9	10.3	17.6	16	10.8
Efficiency (%)					
Evaporating Temp.°F	50	45	50	45	30
Condensing Temp.°F	130	130	100	100	110
Ambient Temp.°F	95	95	95	95	95
Liquid Temp.°F	115	115	85	85	95
Return Gas Temp.°F	65	95	65	65	50

Nominal Performance Data @50Hz (±5) based upon 72hr run-in

Mechanical Data

Bore X Stroke (in)	2 x 1.004	Speed (rpm)	2950
Displacement (in ³ /rev)	-	IPRV Setting ΔP(psi)	400/500
Displacement (ft ³ /hr.)	-	Refrigerant Charge Limit (lbs)	5.5

Electrical Data

RLA :	8.20	UL Approval :	SA5470	Motor Res. In Ohms (Ω)±5%		
LRA :	62.00	CE Approval :	Yes	T1-T3 (C-R)	T1-T3 (C-S)	T2-T3 (S-R)
MCC :	16	CCC Approval	Yes	2.65	2.65	2.65
Voltage Range :	342/457					
Protection Type :	Internal Line Break					

Electrical Accessories Components

Start Relay :	0					
Start Cap (μF/d/volts) :						
Run Cap (μF/d/volts) :	(Parenthesis Denote Med. Torque Components)					
PTCR Start Device : Ceramite P/N :	PTCR Start Device : AC Ohms :					
Crankcase Heater Vendor P/N :	Sensata 8HT5					
Type-watts :	PCTR - 30					

Misc. Technical Info

Oil Name :	3GS Mineral Oil	Polyolester 32BCE			
Oil Spec :	581003	CE Approval :	Recharge :		
Viscosity : (cSt @40°C)	29.5				
					Weight Net
Sound Power (dBA) :	Internal Free Volume (in ³)	Max. Compressor Height (in)	Net (lbs)	Ship (lbs)	
	568	16.125	83	87.5	

Certificate Marks

REV. DATE 22-10-2020

C/N No. 0004/20