

System : English Refrigerant : R22 Series Family : B  
Compressor Model : H29B26UABH Revision : 0 BOM ID : -

**Techninal Specifications**

Voltage	Phase	Frequency
240-220	1	50

Application	H	Evaporator temperature Range	-20 °F to 55 °F
-------------	---	------------------------------	-----------------

**Nominal Performance Data @50Hz**

Performance	ARI	ASRET	13 SEER B	ARI (45/100)	HEATPUMP
	265	265	265	265	265
Capacity (Btu/hr.)	30700	26200	40000	35000	20300
Motor Input (Watt)	2110	2020	1560	1600	1590
Current (Amp)	10.26	9.75	7.12	7.63	7.84
EER (Btu/W-hr.)	11.9	10.8	20.5	18.1	11.2
Efficiency (%)					
Evaporating Temp.°F	50	45	50	45	30
Condensing Temp.°F	130	130	100	100	110
Ambient Temp.°F	95	95	95	95	95
Liquid Temp.°F	115	115	85	85	95
Return Gas Temp.°F	65	95	65	65	50

Nominal Performance Data @50Hz (±5) based upon 72hr run-in

**Mechanical Data**

Bore X Stroke (in)	1.73 x 0.618	Speed (rpm)	2950
Displacement (in <sup>3</sup> /rev)	-	IPRV Setting ΔP(psi)	450/550
Displacement (ft <sup>3</sup> /hr.)	-	Refrigerant Charge Limit (lbs)	6

**Electrical Data**

RLA :	9.60	UL Approval :	SA5470	Motor Res. In Ohms (Ω)±5%		
LRA :	58.00	CE Approval :	Yes	T1-T3 (C-R)	T1-T3 (C-S)	T2-T3 (S-R)
MCC :	18	CCC Approval	No	2.62	1.18	3.8
Voltage Range :	198/264					
Protection Type :	Internal Line Break					

**Electrical Accessories Components**

Start Relay :	GE 3ARR3 *10S*	
Start Cap (μFd/volts) :	145-175/250	
Run Cap (μFd/volts) :	40/370	(Parenthesis Denote Med. Torque Components)
PTCR Start Device : Ceramite P/N :	305C19	PTCR Start Device : AC Ohms : 20
Crankcase Heater Vendor P/N :	Sensata 8HT5	
Type-watts :	PCTR - 30	

**Misc. Technical Info**

Oil Name :	3GS Mineral Oil	Polyolester 32BCE			
Oil Spec :	581003	CE Approval :	Recharge :		
Viscosity : (cSt @40°C)	29.5	35	32		
				Weight Net	
Sound Power (dBA) :	Internal Free Volume (in <sup>3</sup> )	Max. Compressor Height (in)	Net (lbs)	Ship (lbs)	
	340	13.75	66	69.5	

Certificate Marks