



Classification : Specification for Compressor		Written By		Noppadol Yomkaew	
		Approved By		Korakot Intraratat	
Subject : NH56VNHT		Issued Date		2009-05-06	
		Document No.		SPC99O452.02	
				Revised H	
1.Compressor data					
Type		Rotary			
Displacement		cm ³ /rev.		56.9	
		in ³ /rev.		3.5	
2.Motor data					
Motor type		Single phase induction motor (Permanent Split Capacitor)			
Motor protection		Internal			
Nominal output		W		2700	
Nominal revolution		rpm		2850/2880	
LRA		A		79/81	
Insulation class		E			
Motor resistance (20 °C)					
Main winding		Ohm		0.66	
Aux winding		Ohm		1.58	
3.Refrigerant					
Type		R-22			
4.Oil					
Type		NM56EP			
Charge amount		L (in ³)		1.30 (79.3)	
5.Mass (include.oil)		kg (lbs)		32.2 (71.0)	
6.Compressor power source					
Rated voltage		V		220-240 (within ±10%)	
Rated frequency		Hz		50	
Phase		Ø		1	
7.Performance					
Refrigerating capacity (±5%)		W		10572	
		BTU/hr		36072	
				36392	
Motor input (±5%)		W		3450	
				3620	
COP		W/W		3.06	
				2.95	
EER		BTU/hr.W		10.46	
				10.05	
Current		A		15.8	
				15.9	
Note: Conditions		ASRE-T		ASRE-T	
Evaporating temp.		°C (°F)		7.2 (45.0)	
				7.2 (45.0)	
Condensing temp.		°C (°F)		54.4 (129.9)	
				54.4 (129.9)	
Return gas temp.		°C (°F)		35.0 (95.0)	
				35.0 (95.0)	
Ambient temp.		°C (°F)		35.0 (95.0)	
				35.0 (95.0)	
Liquid temp.		°C (°F)		46.1 (115.0)	
				46.1 (115.0)	
Power source		V/Hz		220/50	
				240/50	
Cooling performance curve		PCS138A			
8.Lowest starting voltage		V		Drop 176 (at 10.3kg/cm ² G balancing pressure)	

Please follow to the general specification for NH (NOKS-CF0156)



Classification : Specification for Compressor	Issued Date	2009-05-06
Subject : NH56VNHT	Document No.	SPC99O452.02
Outline drawing	SC01D134	
Wiring diagram	SC01D050	
Running capacitor	SC01D502H09	60 MFD 420 VAC
Crank case heater		38 W
Terminal parts accessories		
Terminal parts assy	SC01D020	
Terminal cover	CR25C046H01	1 pce.
Gasket	SC26D054H01	1 pce.
Clip	CR38D179H01	1 pce.
Mounting accessories (1)		
Mounting parts	SC01D465	
Rubber mount	SC31D009H01	4 pcs.
Mounting accessories (2)		
Mounting parts	CS01D371	
U. rubber	CR31D176H01	4 pcs.
Spring	CR39D181H01	4 pcs.
L. rubber	CR31D175H01	4 pcs.
Optional accessories [Use with (2)]		
Top support parts	SC01D019	
Rubber support	CR31D180H01	1 pce.
Cap	CS01D238H01	1 pce.



Classification : Specification for Compressor	Issued Date	2009-05-06
Subject : NH56VNHT	Document No.	SPC99O452.02
Pressure		
Condensing	1.03 ~ 2.60 MPaG [149.3 ~ 377 psiG]	
Evaporating	0.26 ~ 0.69 MPaG [37.7 ~ 100 psiG]	
Compression ratio	8 or less	
Abnormal rise in pressure	3.92 MPaG [568.5 psiG] or less	
Temperature		
Condensing	28 ~ 65 °C	
Evaporating temperature	-10 ~ 15 °C	
Discharge gas (max)	120 °C (In case of Heat pump or De-humidifier, this limit is 115 °C)	
Suction gas superheat	Must be over 0 °C - No liquid-back	
Discharge gas superheat	20 ° or more	
Outdoor ambient temp.	-Air Cond.: 20 °C ~ 43 °C -Heat pump: -10 ~ 43 °C	
Electrical		
Reverse phase (rotation)	Not possible	
ON / OFF		
ON/OFF frequency	Less than 170,000 cycles	
ON/OFF cycle	-The ON/OFF cycle shall be a maximum of 10 times/hour. -OFF time shall be the time until the high side pressure reach to balance pressure (more than 3 minutes)	
Piping stress	3.5 kg/mm ² or less at start and stop condition (1.8 kg/mm ² during operation)	
Refrigerant circuit		
Maximum refrigerant charge	3.0 kg No accumulator <2.0 kg	
Piping vibration	Maximum 0.8 mm.	
Inclination of compressor	Within 5°	